Abstandstabelle KBULEDHH/230 ERT-LED für ebene Fluchtwege
Distance table KBULEDHH/230 ERT-LED for plane emergency routes

Montagehöhe (m) *Mounting level (m)*					
2.00	6.97	16.50	14.69	8.24	3.33
2.50	8.18	18.99	16.85	9.00	3.57
3.00	9.23	21.29	18.76	9.68	3.70
3.50	9.62	23.41	20.49	10.26	3.75
4.00	10.42	25.35	22.07	10.50	3.73

Die Abstandstabelle basiert auf folgenden Parametern: Wartungsfaktor: 0.8; Notbeleuchtungsfaktor 1.00; Minimale Beleuchtungsstärke auf der Mittellinie: 1.00 lux; Minimale Beleuchtungsstärke auf der halben Rettungswegbreite: 0.50 lux; Gleichmäßigkeit auf der Mittellinie maximal 40:1; Breite des Rettungsweges 2.00m

The distance table is based on the following parameters: Maintenance factor: 0.8; emergency lighting factor 1.00; Minimum illumination on the center line: 1.00 lux; Minimum illumination on the half width of the rescue route: 0.50 lux, uniformity on the midline maximum 40:1; Width of the rescue route 2.00m

Maasewers Ersatzstromtechnik GmbH | Nixhütter Weg 116 | 41466 Neuss
Tel: 02131 34 487-0 | Fax: 02131 34 487-29
info@maasewers.de | www.maasewers.de